





REV.	DESCRIPTION	DATE
—	RELEASE	Mar. 12, 2002
1		
2		



RECOMMEND P.C.B. LAYOUT
BOTTOM VIEW


MATERIAL

- HOUSING : POLYESTER (UL 94V-0), BLACK.
- TERMINAL : PHOSPHOR BRONZE (t=0.40mm)

SPECIFICATION

- CURRENT RATING : 3 AMP. MAX.
- DIELECTRIC WITHSTANDING VOLTAGE .
800V AC R.M.S. FOR ONE MINUTE.
- INSULATION RESISTANCE : 5000M OHMS MIN.
AT 500V DC
- CONTACT RESISTANCE : 30m OHMS MAX.
- OPERATING TEMPERATURE : -55°C TO +105°C

ORDER INFORMATION :



TOTAL NO. OF POS.	DIMENSIONS			TOTAL NO OF POS	DIMENSIONS		
	A	B	C		A	B	C
6	14.22[.560]	10.36[.408]	5.08[.200]	44	62.48[2.460]	58.62[2.308]	53.34[2.100]
8	16.76[.660]	12.90[.508]	7.62[.300]	48	67.56[2.660]	63.70[2.508]	58.42[2.310]
12	21.84[.860]	17.98[.708]	12.70[.500]	50	70.10[2.760]	66.24[2.608]	60.96[2.400]
16	26.92[1.060]	23.06[.908]	17.78[.700]	60	82.80[3.260]	78.94[3.108]	73.66[2.900]
20	32.00[1.260]	28.14[1.108]	22.86[.900]	62	85.34[3.360]	81.48[3.208]	76.20[3.000]
24	37.08[1.460]	33.22[1.308]	27.94[1.100]	64	87.88[3.460]	84.02[3.308]	78.74[3.100]
26	39.62[1.560]	35.76[1.408]	30.48[1.200]	70	95.50[3.760]	91.64[3.608]	86.36[3.400]
28	42.16[1.660]	38.30[1.508]	33.02[1.300]	72	98.04[3.860]	94.18[3.708]	88.90[3.500]
30	44.70[1.760]	40.84[1.608]	35.56[1.400]	80	108.20[4.260]	104.34[4.108]	99.06[3.900]
32	47.24[1.860]	43.38[1.708]	38.10[1.500]	86	115.82[4.560]	111.96[4.408]	106.68[4.200]
34	49.78[1.960]	45.92[1.808]	40.64[1.600]	100	133.60[5.260]	129.74[5.108]	124.46[4.900]
36	52.32[2.060]	48.46[1.908]	43.18[1.700]	108	143.76[5.660]	139.90[5.508]	134.62[5.300]
38	54.86[2.160]	51.00[2.008]	45.72[1.800]	120	159.00[6.260]	155.14[6.108]	149.86[5.900]
40	57.40[2.260]	53.54[2.108]	48.26[1.900]	—	—	—	—

TOLERANCE .0-±.0.30 [.012] .00=±0.20 [.008] .000=±.XXX .0000=±. ANG.=±3°	DRAWER <i>Katherine</i> CHECK <i>PLB</i> APP'D <i>Wisaly</i>	 ASTRON TECHNOLOGY CORP. NAME CARD EDGE CONNECTOR 2.54mm PITCH, P.C.B. MOUNT VERTICAL
 UNITS : mm [inch]	PRODUCT SPEC. — 101-0004	
SCALE NONE SIZE A4	SHEET 1 OF 1	REV. A
DRAW NO. C152-0603		10002