


REV.	DESCRIPTION	DATE
—	RELEASE	Dec. 05, 2003
1		
2		



RECOMMEND P.C.B. LAYOUT  
TOP VIEW


**MATERIALS**

1. HOUSING : HI.-TEMP. PLASTIC (UL 94V-0).
2. TERMINAL : COPPER ALLOY, GOLD PLATING ON CONTACT AREA, TIN PLATING ON SOLDER TAIL.

**SPECIFICATION**

1. CURRENT RATING : 0.5 AMP. MAX.
2. DIELECTRIC WITHSTANDING VOLTAGE : 500V AC R.M.S. FOR ONE MINUTE.
3. INSULATION RESISTANCE : 1000M OHMS MIN. AT 500V DC.
4. OPERATING TEMPERATURE : -25°C TO +60°C.
5. MAX. PROCESSING TEMP. : 230°C FOR 30 ~ 60 SECONDS.

**ORDER INFORMATION :**



PIN NUMBER	CONTACT LENGTH±0.15 [±.006]
25, 26	3.50 [.138]
ALL OTHER PINS	4.25 [.167]
1, 13, 38, 50	5.00 [.197]

TOLERANCE .0=±0.30 [.012] .00=±0.20 [.008] .000=±.XXX .0000=±. ANG.=±3'	DRAWER <i>PUE</i>	<b>Astron</b> ASTRON TECHNOLOGY CORP.
CHECK <i>Katherlin</i>	APP'D <i>LJON</i>	
UNITS : mm [inch]	PRODUCT SPEC. —	NAME MEMORY CARD CF CARD, (TYPE I, II) 1.27mm PITCH P.C.B. MOUNT, SMT, MALE (NORMAL TYPE)
SCALE NONE	SIZE A4	DRAW NO. C254-7148
SHEET 1 OF 1	REV. A	10019