REV.	DESCRIPTION	DATE
—	RELEASE	Apr 15, 2002
1		
2		



E=(NO. OF POSITION PER ROW)x2.00±0.40
(NO. OF POSITION PER ROW)x.079±.016
F=(NO. OF POSITION PER ROW−1)x2.00
(NO. OF POSITION PER ROW−1)x.079





MATERIALS

1 HOUSING · HI−TEMP. PLASTIC (UL 94V−0), BLACK.
2 TERMINAL · S.Q. 0.50mm BRASS.

SPECIFICATION

1. CURRENT RATING : 1 AMP MAX
2. DIELECTRIC WITHSTANDING VOLTAGE : 800V AC R.M.S. FOR ONE MINUTE.
3. INSULATION RESISTANCE : 5000M OHMS MIN. AT 500V DC.
4. OPERATING TEMPERATURE : −55°C TO +105°C.
5. MAX. PROCESSING TEMP. : 230°C FOR 30 ~ 60 SECONDS.

ORDER INFORMATION :

27 − 24 08 1 − 2 ** − * G

- 27 − 24 : SERIES CODE
- 08 : TYPE 08
- 1 : WITHOUT POST
- 2 : DUAL ROWS
- ** : NUMBER OF POSITION PER ROW
- * : CONTACT PLATING OPTIONS
  - 1 : GOLD FLASH
  - 2 : .000010" GOLD
  - 3 : .000015" GOLD
  - 5 : .000030" GOLD
- G : GOLD PLATING ON SOLDER TAIL



RECOMMEND P.C.B. LAYOUT
TOP VIEW

TOLERANCE .0=±0.30 [.012] .00=±0.20 [.008] .000=±.XXX .0000=±. ANG.=±3°	DRAWER YUE	Astron	ASTRON TECHNOLOGY CORP.
	CHECK Katherine		
	APP'D ALEX	NAME	POST HEADER 2.00mm PITCH, P.C.B. MOUNT SMT
UNITS : mm [inch]	PRODUCT SPEC. —	DRAW NO.	C332−4002
SCALE NONE / SIZE A4	SHEET 1 OF 1 / REV. A		05005