





REV.	DESCRIPTION	DATE
—	RELEASE	Mar. 15, 2002
1		
2		



RECOMMEND P.C.B. LAYOUT
BOTTOM VIEW

MATERIALS

- 1 HOUSING : POLYESTER (UL 94V-0), BLACK
2. TERMINAL : PHOSPHOR BRONZE.
3. SHIELD : BRASS, TIN PLATING. (t=0.30mm)
4. SPRING : STAINLESS STEEL. (t=0.20mm)

SPECIFICATION

1. CURRENT RATING : 1 AMP. MAX.
2. DIELECTRIC WITHSTANDING VOLTAGE : 500V AC R.M.S. FOR ONE MINUTE.
3. INSULATION RESISTANCE : 100M OHMS MIN. AT 500V DC
4. CONTACT RESISTANCE : 30m OHMS MAX.
5. OPERATING TEMPERATURE : -25°C TO +85°C.
6. DURABILITY : 1000 CYCLES.
7. MATING FORCE : 0.5 ~ 4.5kgs.
8. UNMATING FORCE : 0.5 ~ 4.5kgs.

ORDER INFORMATION

13 - 0601 - 10 - * T

SERIES CODE | NUMBER OF POSITION | TIN PLATING ON SOLDER TAIL

CONTACT PLATING OPTIONS

- 1 : GOLD FLASH
- 2 : .000010" GOLD
- 3 : .000015" GOLD
- 5 : .000030" GOLD

TOLERANCE .0=±.30 [.012] .00=±.20 [.008] .000=± XXX .0000=± ANG.=±3°	DRAWER <i>Katherlin</i> CHECK <i>Pue</i> APP'D <i>Wisely</i>	 ASTRON TECHNOLOGY CORP. NAME MINI CIRCULAR DIN P.C.B MOUNT RIGHT ANGLE FULL METAL SHIELD, FEMALE WITH SPRING
UNITS : mm [inch]	PRODUCT SPEC —	
SCALE NONE	SIZE A4	DRAW NO. C536-0104
SHEET 1 OF 1	REV A	08005